

TBM3030 600A AC

- Jaw size 26mm
- Large LCD display
- Diode
- Continuity
- Relative zero
- Data hold



3^{-3/4} Digits
4000 Counts

CAT III
300V
IEC61010-1

LISTED
UL

Meter
Supplied With
Certificate of
Conformance

Technical Specification


AC Current	40,600A
DC Voltage	400m,4,40,400,600V
AC Voltage	4,40,400,600V
Resistance	400,4K,40K,400K,4M,40MΩ
Frequency	5Hz to 100KHz
Capacitance	500n,5μ,50μ,500μ,3000μF
Accuracy	
AC Current	±1,9%+ 8 Digit
DC Voltage	±1,0%+ 4 Digit
AC Voltage	4,40,400V ±1,5% + 5 Digit 600V ±2,0% + 5 Digit
Resistance	4K,40K,400KΩ ± 0,6%+4 Digit 4MΩ ± 1,0% + 4 Digit 40MΩ ± 2,0% + 4 Digit
Frequency	± 0,5% + 4 Digit
Capacitance	± 3,5% + 6 Digit

Model Specification

Accessories	Carry Pouch
Dimensions (mm)	190(L) x 63(W) x 32(H)
Power Source	3V CR2032 (TBMBATT)
Weight	187g

TBM126 600A AC Dual Display

- Jaw size 26mm
- Large LCD display
- Diode
- Continuity
- Relative zero
- Data hold



3^{-3/4} Digits
4000 Counts

CAT III
600V
IEC61010-1

LISTED
UL

Meter
Supplied With
Certificate of
Conformance

Technical Specification

AC Current	40,600A
DC Voltage	400m,4,40,400,600V
AC Voltage	4,40,400,600V
Resistance	400,4K,40K,400K,4M,40MΩ
Frequency	5Hz to 100KHz
Temperature	-20°C to 300°C
Capacitance	500n,5μ,50μ,500μ,3000μF
Accuracy	
AC Current	±1,9%+ 8 Digit
DC Voltage	±1,0%+ 4 Digit
AC Voltage	4,40,400V ± 1,5% + 5 Digit 600V ± 2,0% + 5 Digit
Resistance	4K,40K,400KΩ ± 0,6% +4 Digit 4mΩ ± 1,0% + 4 Digit 40mΩ ± 2,0% + 4 Digit
Frequency	±0,5% + 4 Digit
Temperature	±2,0 % + 3°C
Capacitance	±3,5% + 6 Digit

Model Specification

Accessories	Carry Pouch, Temp Probe
Dimensions (mm)	190(L) x 63(W) x 32(H)
Power Source	2 x 3V CR2032 (TBMBATT)
Weight	187g

TBM072 600A AC AmpTip™ Jaws

- Jaw size 30mm
- Amptip™ low current range
- Large LCD display
- Rotary selector switch
- Continuity
- Data hold
- EF Detection



3^{-5/6} Digits
6000 Counts

LISTED
UL

CAT III
600V
IEC61010-1

Meter
Supplied With
Certificate of
Conformance



Technical Specification

AC Current	40,600A
DC Voltage	400m,4,40,400,600V
AC Voltage	4,40,400,600V
Resistance	600,6K,60KΩ
Frequency	5Hz to 100KHz
Accuracy	
AC Current	±1,8%+ 5 Digit
DC Voltage	±1,0%+ 5 Digit
AC Voltage	4,40,400V ± 1,5% + 5 Digit 600V ± 1,2% + 7 Digit
Resistance	4K,40K,400KΩ ± 0,6% +4 Digit 4mΩ ± 1,0% + 4 Digit 40mΩ ± 2,0% + 4 Digit
Frequency	±0,5% + 4 Digit

Model Specification

Accessories	Carry Pouch
Dimensions (mm)	223(L) x 76(W) x 37(H)
Power Source	2 x 1.5V AAA
Weight	186g

TBM076 600A AC AmpTip™ Jaws

- Jaw size 30mm
- Amptip™ low current range
- Large LCD display
- Backlit
- 3 Phase rotation for mains
- 3 Phase rotation for motors
- Temperature
- EF Detection
- Rotary selector switch
- Continuity
- Data hold



3^{-5/6} Digits
6000 Counts



CAT III
600V
IEC61010-1

LISTED
UL

Meter
Supplied With
Certificate of
Conformance



Technical Specification

AC Current	40,600A
DC Voltage	400m,4,40,400,600V
AC Voltage	4,40,400,600V
Resistance	600,6K,60KΩ
Frequency	5Hz to 100KHz
Temperature	-40°C to 400°C
Capacitance	200μ,2000μF
Accuracy	
AC Current	±1,8%+ 5 Digit
DC Voltage	±1,0%+ 5 Digit
AC Voltage	4,40,400V ± 1,5% + 5 Digit 600V ± 1,2% + 7 Digit
Resistance	4K,40K,400KΩ ± 0,6% +4 Digit 4mΩ ± 1,0% + 4 Digit 40mΩ ± 2,0% + 4 Digit
Frequency	±0,5% + 4 Digit

Model Specification

Accessories	Carry Pouch, Temp probe
Dimensions (mm)	223(L) x 76(W) x 37(H)
Power Source	2 x 1.5V AAA
Weight	186g

TBM086 1000A AC AmpTip™ Jaws

- Jaw size 51mm
- Amptip™ low current range
- Large LCD display
- Backlit
- 3 Phase rotation for mains
- 3 Phase rotation for motors
- Temperature
- EF Detection
- Rotary selector switch
- Continuity
- Data hold
- Peak RMS 80ms in-rush current



3^{-5/6} Digits
6000 Counts



CAT III
1000V
IEC61010-1

LISTED
UL

Meter
Supplied With
Certificate of
Conformance



Technical Specification

AC Current	60, 600, 1000A
DC Voltage	600, 1000V
AC Voltage	600, 1000V
Resistance	600,6K,60KΩ
Frequency	5Hz to 400KHz
Temperature	-40°C to 400°C
Capacitance	200μ,2000μF
Accuracy	
AC Current	±1,8%+ 5 Digit
DC Voltage	±1,0%+ 5 Digit
AC Voltage	4,40,400V ± 1,5% + 5 Digit 600V ± 1,2% + 7 Digit
Resistance	4K,40K,400KΩ ± 0,6% +4 Digit 4mΩ ± 1,0% + 4 Digit 40mΩ ± 2,0% + 4 Digit
Frequency	±0,5% + 4 Digit

Model Specification

Accessories	Carry Pouch, Temp probe
Dimensions (mm)	258(L) x 94(W) x 44(H)
Power Source	2 x 1.5V AA
Weight	312g

5-IN-1 CLAMP METERS

The new Amptip™ Digital Clamp Meter with more features!



Applies to the following new models: TBM076, TBM086, TBM079 and TBM089